

## ETR-3400

### 1/32 DIN Temperature Controller with Smarter Logic®



- Automatic Tuning of PID Parameters
- Universal Sensor Input
- Selectable Set Point or Process Value Display
- Analog Input for Remote Set Point Adjustment
- Event Input
- Loop Break Alarm
- Heater Break Alarm
- 5 Per Second Sample Rate
- Digital Communications
- NEMA 4X/IP65
- 3 Year Warranty

#### Description

The ETR-3400 with **Smarter Logic** offers extensive features that are rarely available on a 1/32 DIN controller. In addition to universal field selectable inputs, **auto tuning of PID parameters** and a selection of various control outputs, this controller has an additional analog input and an event input, an analog output or digital communications and other software features which make this controller stand out among 1/32 DINs.

#### Flexible Second Input:

The control sensor input is the primary input. The second input can be set up as a CT (current transformer) input to monitor the actual heater current and alarm if a heater is lost. The second input can also be used as a remote set point, or this input can make the controller a differential controller via a temperature transmitter (the difference in temperature between input 1 and 2).

#### Event Input:

The event input can be used for various functions: selecting between set point 1 and set point 2, between PID1 and PID2 parameters, resetting the alarms, disabling outputs, or locking out the operator parameters.

#### Analog Retransmit:

This analog output can retransmit to a PLC or recorder the Process value, input 2 value, the difference between input 1 and 2, the set point, the output 1 or 2 value, or the deviation between the set point and Process variable.

#### Other Features:

- The bumpless transfer on a sensor break continues to switch the output at the same percentage to prevent a possibly damaging change in output
- Sensor sample rates of 5 times per second allow controlling processes such as pressure and flow.
- NEMA 4X front panel rating can be used in applications requiring washing with a direct spray.
- Up to 3 outputs provide flexibility.
- Dwell Timer is excellent for cooking or other batch applications.
- Digital Communications permits networking with other controllers and computers.

#### External Lockout Code

- Prevents accidental or unauthorized changes

#### Set Point/Process Parameter Display

- Process display updated 5 times per second
- Menu and error codes
- Output Percentage
- Calibration parameter
- Selectable set point or process value

#### Output 1 Indicator

#### Output 2 Indicator

#### Alarm 1 Indicator

#### Non-Volatile Memory

Retains process parameters when power is off



Scroll Key      Up Key      Down Key

#### NEMA 4X Front Panel

- Water and corrosion proof

#### Automatic Tuning

- Eliminates complicated and time consuming manual tuning procedures
- Smarter Logic practically eliminates overshoot and temperature variations.
- Universal Input
- Analog Input for remote set point adjustments
- Heater Break alarm
- Serial Communications or analog retransmission of process value

## ETR-3400

### 1/32 DIN Temperature Controller with Smarter Logic® (cont'd.)

#### Control Specifications

##### UNIVERSAL INPUT SELECTIONS

Display in temperature or engineering units  
Input Set 1

- Input 1:** Thermocouple - J,K,T,E,B,R,S,N,L  
RTD-PT 100 DIN, PT100 JIS  
Current or Voltage - 4-20mA,  
0-20mA, 0-1V, 0-5V, 1-5V and 0-10V
- Input 2:** Analog input 4-20mA, 0-20mA,  
0-1V, 0-5V, 1-5V and 0-10V  
CT for heater break  
Event input

##### CONTROL FEATURES

- Temperature Range:** Selectable
- Set Point:** Full range adjustable
- Control Modes:**  
All Models can be configured as:
- On/off, Proportional (P)
  - Proportional w/manual reset
  - Proportional/Integral (PI)
  - Proportional Derivative (PD)
  - Proportional/Integral/Derivative (PID)

##### Heating and Cooling

- Proportional Band:** 0-900°F (0-482°C)
- Integral (Reset):** 0-1000 Seconds
- Derivative (Rate):** 0-360 Seconds
- Ramp Rate:** 0-99.9°F (0-55.5°C)/Minute
- Dwell Timer:** 0-430 minutes
- Anti-Reset (Wind-up):** Inhibits integral action outside proportional band
- Cooling:** Adjustable dead band from -199.9 to +199°F/-110.0 - +111.0°C
- Manual Mode:** Configurable or automatic transfer to open loop control and secondary output
- Heating or Cooling Cycle Time:** 0.1 to 100.0 seconds
- Sensor Break Protection:** Configurable status of control and secondary outputs

**Control Action:** Selectable - Direct action for cooling; reverse action for heating

##### POWER

- Supply Voltage:** 90-264Vac, 50/60Hz; 20-23VAC/VDC optional
- Consumption:** Less than 15VA
- Data Retention:** 10 Years (EEPROM)

##### OUTPUTS

- Main output with 2 optional independent secondary outputs
- Relay:** SPST relay rated 2A, 240V maximum resistive load,
- Pulsed Voltage:** 5V/30mA SSR Drives (Code 2)  
14V/40mA SSR Drives (Code C)
- Current:** 4-20mA/0-20mA
- Voltage:** Isolated 0-10V, minimum impedance 500K ohms
- Triac:** 1A/240VAC
- Secondary Output (A1):** 5V/30mA SSR Drives (Code 2)  
14V/40mA SSR Drives (Code C)
- Secondary Output (A2):** Form A Relay - 2A/240VAC  
Alarm functions: Dwell timer, Deviation hi/low alarm, PV1 High/Low alarm, PV2 High/Low alarm, PV1 or PV2 High Low alarm, PV1- PV2 High Low alarm, Loop break alarm, Sensor Break alarm
- Alarm Mode:** Normal, latching, hold, latching/hold
- Communications:** RS-485, RS-232 serial
- Analog Output:** 4-20mA/0-20mA. 1-5V/0-5V analog retransmission of set point, output % and deviation

##### INDICATION

- 4-Digit red .4" LED Process Value Display
- Selectable Decimal Placement:** For normal or high resolution display. Example: 0000; 000.0; 00.00; or 0.000
- °F/°C:** Selectable with 2 LED indicators
- Sample Rate:** 5 Samples/second

##### SPECIFICATIONS

- Accuracy:** ±0.1% of span, ± least significant digit
- Control Stability:** ±0.15% (typical) of full scale
- Cold Junction Compensation:** 0.1°C/°C
- External Resistance:** 100 ohms, maximum
- Common Mode Rejection:** 120dB
- Normal Mode Rejection:** 60dB
- Input Impedance:** 10M ohms
- Operating Temperature for Rated Accuracy:** 14-122°F (-10 - 50°C)
- Humidity:** 0-90% RH (non-condensing)
- Insulation:** 20M ohm minimum (500VDC)
- Breakdown:** 2000VAC, 50/60Hz, 1 minute
- Vibration:** 10 - 55Hz, amplitude 1mm
- Shock:** 200m/s<sup>2</sup> (20 grams)
- Dimensions:** 1-7/8"W x 15/16"H x 4-5/16"D (48mmW x 24mmH x 110mmD)  
Depth behind panel: 3-7/8" (76mm)  
Panel Cutout: 7/8"x1-25/32" (22X45mm)  
Weight: 4oz. (113 grams)

## ETR-3400

### 1/32 DIN Temperature Controller with Smarter Logic® (cont'd.)

#### Ordering Information

Complete the model number using the matrix provided.

#### Accessories

CC94-1	RS-232 Interface Cable (2M)
CT94-1	Current Transformer for CT Input/Heater Break Option
SNA10A	Smart Network Adaptor for Third Party Software. Converts one channel of RS-485 or RS-422 to RS-232 Network.
SNA10B	Smart Network Adapter for ETR-Net Software. Converts 255 channels of RS-485 or RS-422 to RS-232 Network.

Model	Microprocessor based temperature controller with Smarter Logic®						
ETR-3400	1/32 DIN; universal field selectable inputs; PID autotuning; selection of various control outputs; additional analog and event inputs; analog or digital communications						
	<b>Code</b>	<b>Power Input</b>					
	4	90-264 Vac, 50/60 Hz					
	5	11-26Vac or Vdc					
			<b>Code</b>	<b>Signal Input</b>			
			1	Standard Input			
				Input 1 - Universal input Thermocouple J,K,T,E,B,R,S,N,L RTD: PT100 DIN, PT100 JIS Current: 4-20mA, 0-20mA Voltage: 0-1V, 0-5V, 1-5V, 0-10V			
				Input 2 - CT: 0-50 Amp, AC Current Transformer*** Analog Input: 4-20mA, 0-20mA, 0-1V, 0-5V, 1-5V, 0-10V			
				Input 3 - Event Input (EI)**			
			<b>Code</b>	<b>Output 1</b>			
			1	Relay rated 2A/240Vac			
			2	Pulsed voltage to drive SSR, 5V/30mA			
			3	Isolated 4 - 20mA/0 - 20mA			
			4	Isolated 1 - 5/0 - 5V*			
			5	Isolated 0 - 10V			
			6	Triac Output 1A/240Vac			
			C	SSR Drive 14V/40mA			
			<b>Code</b>	<b>Output 2/Alarm 2</b>			
			0	None			
			1	Form A Relay 2A/240Vac			
			2	Pulsed voltage to drive SSR, 5V/30mA			
			3	Isolated 4 - 20mA/0 - 20mA*			
			4	Isolated 1 - 5/0 - 5V*			
			5	Isolated 0 - 10V			
			6	Triac Output 1A/240Vac			
			7	Isolated 20V/25mA DC Output Power Supply			
			8	Isolated 12V/40mA DC Output Power Supply			
			9	Isolated 5V/80mA DC Output Power Supply			
			C	SSR Drive 14V/40mA			
			<b>Code</b>	<b>Alarm 1</b>			
			1	5V Logic Output			
			<b>Code</b>	<b>Communications</b>			
			0	None			
			1	RS-485 Interface			
			2	RS-232 Interface**			
			3	Retransmit 4 - 20mA 0 - 20mA*			
			4	Retransmit 1 - 5V/0 - 5V*			
			5	Retransmit 0 - 10V			
<b>ETR-3400</b>	<b>4</b>	<b>1</b>	<b>1</b>	<b>1</b>	<b>1</b>	<b>1</b>	<b>Typical Model Number</b>

\* Range set by front keyboard  
 \*\* Alternative between RS-232 and Event Input  
 \*\*\* Order CT94-1 if Heater Break Function is required