



传声器供电调理设备

MC102 / MC141 / MC104 / MC711 / MC722

型号	MC102	MC141	MC104	MC711	MC722
图示					
输入通道数	2	1	4	1	2
输入通道接口	BNC	BNC	BNC	7-pin LEMO	7-pin LEMO
输出通道数	2	1	4	1	2
输出通道接口	BNC	BNC	BNC	BNC	BNC
频率响应(Hz)	5 ~ 200k	5 ~ 200k	5 ~ 200k	1 ~ 1M	5 ~ 200k
增益档位(dB)	无	× 1, × 10	× 0.1, × 1, × 10	无	-20 dB, 0 dB, 20 dB, 40 dB
极化电压	0 V	0 V	0 V	200 V 或者 0 V	200 V 或者 0 V
前置供电	4 mA	4 mA	4 mA	28 V	28 V 或者 120 V
使用电源	1 × 9 V 电池供电或 220 V	220 V	220 V	220 V	220 V
滤波器	无	无	无	无	Lin, AW, HP, Dir
使用温度范围(°C)	-10 ~ 50	-10 ~ 50	-10 ~ 50	-10 ~ 50	-10 ~ 50
使用湿度范围(RH)	0 ~ 95%	0 ~ 95%	0 ~ 95%	0 ~ 95%	0 ~ 95%
尺寸(mm)	113 × 70 × 45	113 × 70 × 45	310 × 250 × 65	113 × 70 × 45	260 × 60 × 150
重量(g)	160	160	1500	190	1130

